



Lintech Energy Shipping
15.000 DWT CHEMICAL TANKER

MAIN DIMENSION :

LENGTH OVERALL	: 130.00 M
LBP	: 127.00 M
BRADTH	: 22.00 M
DEPTH	: 11.50 M
DRAFT	: 8.50 M

PROPULSION SYSTEM

Main Engine	: 2500 KW 1800 RPM
Gear Box	: Rasio 5 : 1
Propeller	: Dia 5000 mm Fixed Pitch 4 Blades

AUXILIARY EQUIPMENT

Aux Engine	: 2 X 250 Kva
------------	---------------

HULL CONSTRUCTION

Keel Plate Thickness	15 mm
Bottom Plate Thickness	13 mm
Sheer Plate Thickness	14 mm
Center Girder Thickness	12 mm
Side Girder Thickness	10 mm
Floor Plate Thickness	10 mm
Tank Top Thickness	11 mm
Inner Shell Thickness	11 mm
Forepeak Thickness	18 mm

COMPARTEMENT

No Compartement	: 4 Cargo Tanks
Lining	: Stainless Steel

DECK LAY OUT

Windlass	
Ancor	
Chain	

NAUTICAL & COMMUNICATION EQUIPMENT

GMDSS A2 AREA	
SEARCHLIGHT 2 x 230 V, 1000 W	
RADAR FURUNO 1932 MK-2	
GPS NAVIGATOR FURUNO GP-32	
ECHO SOUNDER FURUNO FCV-620	
SART JOTRON TRON SART	
EPIRB JOTRON TRON 40S	
AUTOPILOT ALPHASEAPILOT	
VHF FURUNO FM-2721	
NAVTEX FURUNO NX-700B	
INTERCOM PHONTECH CIS-3100	
SATELLITE COMPASS FURUNO SC-30-E-6	
MAGNETIC COMPASS CASSENS&PLATH 33005	

SAFETY EQUIPMENT

Lifeboat Cap 30 Persons	: 1 Unit
Liferaft	: 4 Unit
Fire Fight System	

CLASSIFICATION :

NKK (Nippon Kaiji Kyokai)

Office: Wira Jatim Industrial Estate

Jl. Mastrap 70, Karangpilang - Surabaya

Telp. : +62-31-7666891; Fax : +62-31-7664604

Email: admin@lintech.co.id Website: www.lintech.co.id